



SpillSmart Organic Peroxide Substance Cabinets provide convenient access to chemicals and liquids frequently used without compromising safety. By storing flammable liquids in this cabinet, you reduce fire risks whilst protecting workers. When storing many different chemicals, it is critical to consult with SDS sheets to ensure incompatible chemicals are segregated to avoid the potential of dangerous explosions or reactions. The manufactures SDS Sheets should be reviewed to determine chemical characteristics and recommended storage practices.

These cabinets meet Australian Standards 2714 and feature a double wall thermal barrier, dual side vents and automated self-closing doors. For added security a key lock door handle and 3 point latch locking system is provided to the 180 degree opening doors. Polyethylene spill collection trays are on each shelf and in the sump to protect against accidental spills. For added protection, additional undercoat etch is used and completed in

a durable high gloss powder coat finish providing excellent chemical resistance.

Designed for:

- Storage of Class 3 Flammable Liquids
- Reducing fire risk
- Protecting workers
- Provide secure storage of flammable liquids
- Practical storage when space is limited

Features:

- 100L Capacity
- H800 x W1100 x D500mm - 100kg
- Double door under bench cabinet with single adjustable shelf
- Double wall thermal barrier
- Alloy contact points – no spark risk
- Holds 24 x 2.5L Winchester Bottles
- Doors open 180 degrees creating easy shelf removal
- Key lock handles and 3 point latch locking
- Optional earthing point and cable provided
- Undercoat etch is used before finishing with a high gloss powder coat finish
- Adjustable levelling feet

ES-C-OPSC-100 100L Organic Peroxide Cabinet



Hazardous Materials
Class 5.2: Organic Peroxide